



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :

H04R 3/02, H03H 21/00

A1

(11) International Publication Number:

WO 97/16942

(43) International Publication Date:

9 May 1997 (09.05.97)

(21) International Application Number: PCT/GB96/02643

(22) International Filing Date: 30 October 1996 (30.10.96)

(30) Priority Data:

9522204.8

30 October 1995 (30.10.95)

GB

(71) Applicant (for all designated States except US): **BRITISH BROADCASTING CORPORATION** [GB/GB]; Broadcasting House, London W1A 1AA (GB).

(72) Inventors; and

(75) **Inventors/Applicants (for US only):** STOTT, Jonathan, High-ton [GB/GB]; British Broadcasting Corporation, Research & Development Dept., Kingswood Warren, Tadworth, Surrey KT20 6NP (GB). WELLS, Nicholas, Dominic [GB/GB]; British Broadcasting Corporation, Research & Development Dept., Kingswood Warren, Tadworth, Surrey KT20 6NP (GB).

(74) Agent: ABNETT, Richard, Charles; Reddie & Grose, 16 Theobalds Road, London WC1X 8PL (GB).


(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, ~~SG~~).

Published

With international search report.

09/781650

(54) Title: METHOD AND APPARATUS FOR REDUCTION OF UNWANTED FEEDBACK



(57) Abstract

The feedback caused between the output (39) and the input (30) of an amplification path (54, 42, 56, 60, 62, 64) is reduced by providing a delay (60) in the amplification path, passing through the amplification path a signal having an auto-correlation function which is substantially a delta function, correlating (72) the said signal before being delayed in the delay with the signal after being delayed in the delay to produce a plurality of correlation coefficients, modifying the signal in the amplification path to provide a modified signal, the modification being provided by a transversal filter (76) controlled by the said plurality of correlation coefficients, and combining (42) the modified signal with the signal in the amplification path so as to reduce the effect of the feedback. The signal having an auto-correlation function which is substantially a delta function may be an added noise signal (70) or may be constituted by the signal being processed itself. The system can be used to reduce "howl-around" in audio situations or feedback in simultaneous coherent re-broadcast transceivers.